Vredo Direct Drills

Renowned worldwide for quality, performance and innovation, Vredo efficient, reliable, responsible direct drills are setting new standards for sustainable agriculture





Vredo's direct drill machines are a must for anyone looking for a professional approach to direct drilling in arable stubble such as cereals and cover crops. The unique double-disc system avoids disturbing the soil and is therefore the most environmentally responsible way of drilling. The uncultivated soil remains contain the organic layer and keeps its solidity, humidity, and structure.

Supplied as standard with

- Seed hopper with a capacity of 1.050 litre.
- From 2.9 up to 5.9 m drilling width. Ensures maximum coverage for sustainable arable farming.
- Gas strut. Opens and closes the lid of the seed hopper smoothly.
- Smooth roller with scraper. Guaranteed sowing depth.
- LED lighting. Clear, bright light ensures safe road transport and clear signals.
- Platform. Helps fill the machine safely.
- Digital hectare counter. Registers the daily and total amount of hectares that have been sown.
- Sight glass. Shows the level in the seed hopper.
- Universal dosing roller. Enables precise dosing of all varieties of seeds (5-300 kg/ha).

Added value options

- Heavy cast iron packer ring roller. Inhibits growth of problem grasses and promotes seed establishment.
- Scraper for packer ring roller. Ensures each moveable packer ring stays clean.
- Electronic Dosing System (EDS). Dosing rate can be adjusted from the tractor cab, for example in bare patches or headlands. The system includes an electronic sensor that gives a clear acoustic and light signal when the seed hopper is empty.
- Cam wheels for fine or coarse seed. Enables small amounts of fine seed or large amounts of coarse seed to be sown.



Drill With Precision

Vredo's exceptional precision seeding system, places each seed accurately at the ideal depth and spacing for optimal germination and uniform crop emergence.



www.campeyagriculture.com

Technical specifications

- Suitable for: arable stubbles and flat/hilly conditions
- Seed dosage: 3 300 kg per hectare (continuously adjustable)
- Sowing depth: 0-25 mm
- Working speed: 10-12 km per hour
- Hydraulic fan: max. 25 litres, 160 bar
- Discs: 2x sharp cutting discs Ø 406 mm and maintenance-free bearings
- Row distance: 7.5 cm

- Elements: suspended elements by a progressive spring for keeping contact with soil
- Turf guard: adjustable
- Smooth roller: guaranteed sowing depth and fillable with liquid for more weight
- Calibration: calibration table and calibration tray
- Mounting: 3-point; CAT 2
- Depth adjustment: top link

Туре	Roller	Weight	Seed hopper volume	Tractor power	GPS working	Transport dimensions (Ixwxh)
DZ 3000O123-01 Agri Air	Smooth	1.280 kg	1.050 litre	100 hp	2.90 m	1.31 x 2.95 x 2.2
DZ 3000O123-01 Agri Air	Packer ring	2.050 kg	1.050 litre	120 hp	2.90 m	1.31 x 2.95 x 2.20 m
DZ 3000O124-01 Agri Twin	Smooth	2.080 kg	1.050 litre	150 hp	4.35 m	1.49 x 3.00 x 2.45 m
DZ 3000O124-01 Agri Twin	Packer ring	3.330 kg	1.050 litre	180 hp	4.35 m	1.49 x 3.00 x 2.45 m
DZ 3000O124-01 Agri Twin	Smooth	2.775 kg	1.050 litre	150 hp	5.90 m	1.49 x 3.00 x 2.90 m
DZ 3000O124-01 Agri Twin	Packer ring	4.365 kg	1.050 litre	180 hp	5.90 m	1.49 x 3.00 x 2.90 m









